

## SPECIFICATIONS

## EMERGENCY

### HOUSING

- Die-Cast Aluminum housing
- Sealed and gasketed
- Offered in white, black, bronze, or nickel finishes

### ELECTRICAL

- Unit can work as Normally-On, Normally-Off, or as a switched circuit
- Universal 120-277V
- Charge rate/power "On" LED light and push-to-test switch for testing
- Standard Operating Temperature: 0°C - 50°C (32°F - 122°F)
- Cold Weather option: -30°C - 50°C (-22°F - 122°F)
- Self Diagnostics are standard, performing a monthly, bi-annual, and annual test
- Photocell sensor is standard for dusk-to-dawn

### ILLUMINATION

- 6W LED lamps standard
- 1275 Lumens in AC mode; 351 Lumens in EM mode

### BATTERY

- 4.8V maintenance-free, NiCd battery
- LVD prevents battery from deep discharge
- Internal transfer switch automatically connects battery to lamp heads for 90-minute emergency illumination
- Two-rate charger initiates battery charge to recharge in battery in 24 hours

### MOUNTING

- Universal knockout pattern on back plate for wall mount
- Threaded opening at top for conduit feed applications

### CODE COMPLIANCE

- UL Listed for Wet Locations
- Meets UL924, NFPA 101, Life Safety Code, NEC, OSHA, Local and State Codes
- CEC Title 20 Certified optional

### WARRANTY

- 5 Year



## DEM-LED Wet Location Die-Cast AC/EM unit

## ORDERING INFORMATION


### CATALOG#

DEM-LED-\*ACEM-PC

\*Specify Color: **BL**ack; **WH**ite; **BR**onze; **NI**ckle

### OPTIONS (Factory Installed)

CW	- Cold Weather (-30°C)
T20	- CEC Title20 Compliant



ELECTRICAL INFORMATION

Catalog #	Input Watts (W)		Input Amps (A)	
	120V	277V	120V	277V
DEM-LED	2.5	2.5	0.04	0.04
DEM-LED-CW	2.8	2.8	0.026	0.026

SPACING GUIDELINES

Model #	Mounting Height (ft)	3' Wide Egress Path		6' Wide Egress Path		Lumens per Head	Head Qty
		Single Unit (ft)	Unit to Unit (ft)	Single Unit (ft)	Unit to Unit (ft)		
DEM-LED	7.5'	25'	29'	18'	22'	351	1 (2 lamps under lens)
	10'	20'	22'	16'	20'		