

**Project** 

**Type** 

**Catalog Number** 

**SPECIFICATIONS** STATE SPECIFIC

## HOUSING

- 20 Gauge steel housing
- Available in white or black finished
- High-impact thermoplastic lamp heads

#### **ELECTRICAL**

- Dual 120/277V standard
- Operating Temperature: 25°C (77°F)

#### **ILLUMINATION**

- Field installable optional third lamp head provided standard with 27W and 50W models

#### **BATTERY**

- Sealed lead acid battery
- Internal transfer switch automatically connects battery to lamp heads for 90-minute emergency illumination
- LVD (Low Voltage Disconnect) prevents battery from deep discharge
- Two-rate charger initiates battery charge to recharge in battery in 24 hours
- 12V models have 14W remote capacity

#### **MOUNTING**

- Universal knockout pattern on back for wall mount
- Side and top knockouts for conduit feed

## **CODE COMPLIANCE**

- UL Listed for Indoor Locations
- Meets UL924, NFPA101, NEC, OSHA, Local and State Codes

### WARRANTY

- 5 Year

## ORDERING INFORMATION

CATALOG#	Description
NYIEM-6V18W	6V, 18W, 9W Lamps
NYIEM-6V27W	6V, 27W, 9W Lamps
NYIEM-12V50W	12V, 50W, 12W Lamps

EX: NYIEM-12V50W

## **OPTIONS (Factory Installed)**

BLK - Black Housing



# **NYIEM NYC Approved Emergency Unit**







