

SPECIFICATIONS

STATE SPECIFIC

HOUSING

- Durable 20 gauge steel housing
- White powdercoat finish standard
- Black finish also available
- Removable chevrons standard
- Available in single, double, or universal face

ELECTRICAL

- Dual 120/277V
- Consumes less 2W or less
- Charge rate/power "On" LED light and push-to-test switch for testing
- Operating Temperature: 10°C - 40°C (50°F - 104°F)

BATTERY

- Sealed Lead Acid Battery
- NiCad Battery also available (NI)
- Low Voltage Disconnect prevents battery from deep discharge
- Internal transfer switch automatically connects battery to lamp heads for 90-minute emergency illumination
- Two-rate charger initiates battery charge to recharge in battery in 24 hours

MOUNTING

- Universal knockout pattern on back plate

CODE COMPLIANCE

- cSAus Listed for Indoor Locations
- Meets UL Requirements
- BAA Compliant
- Meets Local and State Codes

WARRANTY

- 5 Year



NYSTXC
NYC Approved
Steel Combo

ORDERING INFORMATION

MODEL#	Face #	Letter	Housing	Operation	Lamping
NYSTXC	1-Single	R-Red	W-White	6V12W	See Chart
	2-Double			6V18W	
	3-Universal			6V22W-NI	
				6V27W	
				12V27W	
				6V36W	
				12V36W	
				6V42W-NI	
				12V42W-NI	

LAMPING	
LH	- Less Heads
MR06	- 6W MR16 Halogen Lamp - uses PAR18 heads (6V)
MR10	- 10W MR16 Halogen Lamp - uses PAR18 heads (6V, 12V)
MR12	- 12W MR16 Halogen Lamp - uses PAR18 heads (12V)
MR20	- 20W MR16 Halogen Lamp - uses PAR18 heads (12V)
MR35	- 35W MR16 Halogen Lamp - uses PAR18 heads (12V)
LMR02	- 2W MR16 LED Lamp - uses PAR18 heads(12V)
LMR05	- 5W MR16 LED Lamp - uses PAR18 heads(6V, 12V)
LMR07	- 7W MR16 LED Lamp - uses PAR18 heads(6V, 12V)

LAMPING	
10WH	- 10W Halogen Lamps - uses PAR36 heads (6V)
12WH	- 12W Halogen Lamps - uses PAR36 heads (6V, 12V)
20WH	- 20W Halogen Lamps - uses PAR36 heads (6V, 2V)
35WH	- 35W Halogen Lamps - uses PAR36 heads (12V)
3W	- 3W Incandescent Lamp - uses PAR36 heads (6V)
6W	- 6W Incandescent Lamp - uses PAR36 heads (6V)
9W	- 9W Incandescent Lamp - uses PAR36 heads (6V, 12V)
18W	- 18W Incandescent Lamp - uses PAR36 heads (12V)

OPTIONS (Factory Installed)	
B	- Black Housing (replaces W in part number)
SD	- Self Diagnostics
FAI	- Fire Alarm Interface (requires TD option)
IA	- Audible Intermittent Alarm
IV	- Visual Intermittent Alarm (specify voltage)
VM	- Voltmeter
AM	- Ammeter
TD	- Time Delay (specify voltage)

ACCESSORIES (Order Separately)

- SK12-* - 12" Stem Kit (other lengths available)
- *Specify W-White; B-Black; BA-Brushed Aluminum*

